



- .-Downlight led encastrable para instalación en falsos techos
- .-Reflector aluminio , 60° y 90° , UGR inferior a 19 (según modelo)
- .-Dos rendimientos luminicos según necesidades ,
- .-Instalacion encastrada
- .-Posibilidad Emergencia



REFERENCIA	D CORTE	W	Lm 3000	Lm 4000	UGR	CRI	CLAS ENEG	PDF	LDT
DHE 100 HL 60	100	10,2	1.060	1.110	20	80	A+	PDF	LDT
DHE 150 HL 60	150	20,8	2.130	2.210	19	80	A+	PDF	LDT
DHE 200 HL 60	200	29,8	3.070	3.180	18	80	A+	PDF	LDT
DHE 100 HL 90	100	10,2	1.060	1.110	23	80	A+	PDF	LDT
DHE 150 HL 90	150	20,8	2.130	2.210	22	80	A+	PDF	LDT
DHE 200 HL 90	200	20,8	3.070	3.180	22	80	A+	PDF	LDT

REFERENCIA	D CORTE	W	Lm 3000	Lm 4000	UGR	CRI	CLAS ENEG	PDF	LDT
DHE 100 TH 60	100	10,2	1.060	1.110	20	80	A+	PDF	LDT
DHE 150 TL 60	150	10,1	1.100	1.120	16	80	A+	PDF	LDT
DHE 200 TL 60	200	20,4	2.200	2.250	17	80	A+	PDF	LDT
DHE 100 TH 90	100	10,2	1.060	1.110	23	80	A+	PDF	LDT
DHE 150 TL 90	150	10,1	1.100	1.120	20	80	A+	PDF	LDT
DHE 200 TL 90	200	20,4	2.200	2.250	20	80	A+	PDF	LDT